








INDOOR UNITS

WALL-MOUNTED									
		MSY-GL24NA	MSZ-GL24NA	MSZ-FH18NA2	MSZ-EF18NAB	MSZ-EF18NAW	MSZ-EF18NAS	MSZ-HM24NA	MSY-D36NA-8
COOL (BTU/H)	22500	22400	17200	17200	17200	17200	17200	22500	33200
HEAT (BTU/H)	N/A	27600	18000	21600	21600	21600	21600	N/A	35200
SEER	20.5	20.5	22	N/A	N/A	N/A	N/A	20.5	14.5
HSPF	N/A	10	12	N/A	N/A	N/A	N/A	N/A	8.2
ENERGY STAR	YES	YES	YES	NO	NO	NO	NO	YES	NO
SOUND LEVEL AS LOW AS DB(A)	34	32	25	30	30	30	30	34	32
I-SEE SENSOR OPTION	NO	NO	YES	NO	NO	NO	NO	NO	NO
CONTROL OPTIONS AVAILABLE	ALL	ALL	ALL	ALL	ALL	ALL	ALL	ALL	ALL
FILTER TYPE	A, N	E, N	A	A	A	A	A	A, N	A, C
FAN SPEEDS	4 SPEED	3 SPEED	5 SPEED	5 SPEED	5 SPEED	5 SPEED	5 SPEED	4 SPEED	3 SPEED
TIMER	24H	24H	24H	WK, 24H	WK, 24H	WK, 24H	WK, 24H	24H	24H


FLOOR-MOUNTED			HORIZONTAL DUCTED		CEILING RECESSED		AIR HANDLER	
COOL (BTU/H)	17000			17200		15000	36000	
HEAT (BTU/H)	21000			21600		18000	38000	
SEER	21			17.5		16	19.3	
HSPF	11.3			10		9.6	9.5	
ENERGY STAR	YES			YES		NO	NO	
SOUND LEVEL AS LOW AS DB(A)	26			30		31	30	
I-SEE SENSOR OPTION	NO			NO		NO	NO	
CONTROL OPTIONS AVAILABLE	ALL			ALL		ALL	ALL	
FILTER TYPE	A, N			F		F	F	
FAN SPEEDS	5 SPEED			3 SPEED		4 SPEED	3 SPEED	
TIMER	WK, 24H, SL			VARIES BY CONTROL		VARIES BY CONTROL	VARIES BY CONTROL	

OUTDOOR UNITS

SINGLE-ZONE					
		MUZ-GL24NA-U1	MUZ-FH18NA2	MUZ-HM18NA2	MUZ-HM24NA2
COOL (BTU/H)	22400	17200	17200	22500	33200
HEAT (BTU/H)	27600	20200	18000	26000	35200
SEER	20.5	21	18	18	14.5
HSPF	10	12	8.5	8.5	8.2
ENERGY STAR	YES	YES	NO	NO	NO
SOUND LEVEL AS LOW AS DB(A)	55	52	49	54	56
HYPER-HEAT	NO	YES	NO	NO	NO

MULTI-ZONE				
		MXZ-4C36NA2	MXZ-5C42NA2	MXZ-4C36NAHZ
COOL (BTU/H)	35400	40500	36000	60000
HEAT (BTU/H)	36000	45000	45000	66000
SEER	19.2	19.7	19.1	17.4
HSPF	11	10.3	11.3	10.5
MAX ZONES	4	5	4	8
ENERGY STAR	NO	NO	YES	YES
SOUND LEVEL AS LOW AS DB(A)	54	56	49	58
HYPER-HEAT	NO	NO	YES	NO

CONTROLS

THERMOSTATS		
		MHK1
Number of Units Controllable	1	
Fan Speed Settings	5 Speeds	
Scheduling	<ul style="list-style-type: none"> · Separate Heat/Cool scheduling · Set occupied time and desired set temperature · Remote controller learns when to start warm up or cool down so that space is at set temperature at start of occupied time 	
Optimal Start	<ul style="list-style-type: none"> · Hold function · Temporary Schedule Override · Reset to factory default 	
Additional Functions	<ul style="list-style-type: none"> · Setting/releasing of simplified locking for remote control settings can be performed. <ul style="list-style-type: none"> · Locking of all settings · Locking of ON/OFF setting · Locking of system · Locking of fan setting · Locking of temperature · Locking of Clock/Day/Schedule 	
Auto Lock Out Function		